

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 1
Printed: 04/20/2015
Revision: 04/16/2015
Supersedes Revision: 03/27/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Goof Off All Purpose Paint Stripper
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Phone Number: (901)775-0100
Web site address: www.wmbarr.com
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Intended Use: Paint/Varnish Remover
Synonyms: FG762, FG763
Additional Information This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2
Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 4
Acute Toxicity: Inhalation, Category 3
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2A
Carcinogenicity, Category 1B
Toxic To Reproduction, Category 2
Specific Target Organ Toxicity (single exposure), Category 1
Specific Target Organ Toxicity (repeated exposure), Category 2



GHS Signal Word: Danger
GHS Hazard Phrases: H225: Highly flammable liquid and vapor.
H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H350: May cause cancer.
H361: Suspected of damaging fertility or the unborn child.
H370: Causes damage to organs.
H373: May cause damage to organs through prolonged or repeated exposure.
GHS Precaution Phrases: P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 2

Printed: 04/20/2015

Revision: 04/16/2015

Supersedes Revision: 03/27/2015


GHS Response Phrases:

P260: Do not breathe gas/mist/vapors/spray.
P264: Wash hands thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P281: Use personal protective equipment as required.
P235: Keep cool.
P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+311: IF exposed: Call a POISON CENTER or doctor/physician.
P308+313: IF exposed or concerned: Get medical attention/advice.
P311: Call a POISON CENTER or doctor/physician.
P314: Get medical attention/advice if you feel unwell.
P321: Specific treatment see label.
P330: Rinse mouth.
P332+313: If skin irritation occurs, get medical advice/attention.
P337+313: If eye irritation persists, get medical advice/attention.
P362: Take off contaminated clothing and wash before re-use.
P363: Wash contaminated clothing before reuse.
P370+378: In case of fire, use dry chemical powder to extinguish.
P403+233: Store container tightly closed in well-ventilated place.
P405: Store locked up.
P501: Dispose of contents/container according to local, state and federal regulations.

GHS Storage and Disposal Phrases:

Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL		0
PPE		X



HMIS:

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

This product has not been tested as a whole to determine health effects. The health effects listed below are associated with the individual ingredients listed in Section 3.

EYES: Causes eye irritation. May cause tearing, redness, stinging or burning, swelling, and blurred vision. May cause corneal injury.

SKIN: May cause effects ranging from mild irritation to severe pain, and possibly burns, depending on the intensity of contact. Skin absorption may occur.

INHALATION: May cause upper respiratory tract irritation and central nervous system depression with symptoms such as confusion, lightheadedness, dizziness, nausea, vomiting, headache, and fatigue. Causes formation of carbon monoxide in blood which may affect the cardiovascular system and central nervous system, and can cause a lack of oxygen in the blood. Continued exposure may cause unconsciousness, coma, and even death.

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 3

Printed: 04/20/2015

Revision: 04/16/2015

Supersedes Revision: 03/27/2015

INGESTION: May cause nausea, vomiting, and diarrhea. May cause central nervous system excitement, followed by headache, dizziness, and drowsiness. Not expected due to high viscosity, but if vomiting results in aspiration, chemical pneumonia could occur, which may be fatal. Absorption through the gastrointestinal tract may produce central nervous system depression. May cause kidney damage. May cause blurred vision and visual impairment (including blindness).

CHRONIC OVEREXPOSURE EFFECTS: May cause liver and kidney damage. May cause cancer based on animal data (methylene chloride). Prolonged or repeated skin contact may cause defatting and dermatitis.

Methanol has caused birth defects in laboratory animals, but only when inhaled at extremely high vapor concentrations. The relevance of this finding to humans is uncertain.

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal.

ADDITIONAL DATA:

For Methylene Chloride: Alcohol may enhance the toxic effects. May cross the placenta. May be excreted in breast milk. Concurrent exposure to carbon monoxide, smoking, or physical activity may increase the level of carboxyhemoglobin in the blood resulting in additive effects.

TARGET ORGANS: blood, central nervous system, liver, skin, cardiovascular system, eyes, kidney, pancreas, heart, lungs, brain

PRIMARY ROUTES OF ENTRY: skin, eyes, inhalation, ingestion

Medical Conditions Generally Aggravated By Exposure: Diseases of the blood; skin; eyes; liver; kidneys; lungs; pulmonary system; cardiovascular system and respiratory system; alcoholism and rhythm disorders of the heart.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	30.0 -40.0 %	PA8050000
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	15.0 -26.0 %	PC1400000
67-64-1	Acetone {2-Propanone}	<10.0 %	AL3150000
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	<10.0 %	ZE2100000
108-88-3	Toluene {Benzene, Methyl-; Toluol}	<10.0 %	XS5250000
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	< 5.0 %	DA0700000
64-17-5	Ethyl alcohol {Ethanol}	< 5.0 %	KQ6300000
67-63-0	Isopropyl alcohol {sec-Propyl alcohol; IPA; 2-Propanol}	< 5.0 %	NT8050000

Additional Chemical Information Specific percentage of composition is being withheld as a trade secret.

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 4
Printed: 04/20/2015
Revision: 04/16/2015
Supersedes Revision: 03/27/2015

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin:
Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:
Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:
Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:
If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms Of Exposure:

See Potential Health Effects.

Note to Physician:

This product contains methylene chloride and methanol.

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis. Adrenalin should never be given to a person overexposed to methylene chloride.

Methylene Chloride is an aspiration hazard. Risk of aspiration must be weighed against possible toxicity of the material when determining whether to induce emesis or to perform gastric lavage. This material sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. This material is metabolized to carbon monoxide. Consequently, elevations in carboxyhemoglobin as high as 50% have been reported, and levels may continue to rise for several hours after exposure has ceased. Data in experimental animals suggest there is a narrow margin between concentrations causing anesthesia and death.

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 5
Printed: 04/20/2015
Revision: 04/16/2015
Supersedes Revision: 03/27/2015

5. FIRE FIGHTING MEASURES

Flammability Classification:	1B
Flash Pt:	30.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: No data. UEL: No data.
Autoignition Pt:	No data.
Suitable Extinguishing Media:	Use carbon dioxide, dry powder, or alcohol resistant foam.
Unsuitable Extinguishing Media:	Do not use straight streams of water. If water is used, use a water spray or fog.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	Danger! Flammable. Keep away from heat, sparks, flame, and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources. Contact of liquid or vapor with flame or hot surfaces will produce toxic gases and a corrosive residue that will cause deterioration of metal.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	<p>Vapors may cause flash fire or ignite explosively.</p> <p>Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.</p> <p>Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.</p> <p>Large spills: Dike far ahead of spill for later disposal.</p> <p>Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.</p>
---	---

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	<p>Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.</p> <p>Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.</p> <p>Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.</p> <p>Do not spread this product over large surface areas because fire and health safety risks</p>
---	---

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 6
 Printed: 04/20/2015
 Revision: 04/16/2015
 Supersedes Revision: 03/27/2015

will increase dramatically.

Precautions To Be Taken in Storing:

Store in a cool place in original container and protect from sunlight. Exposure to high temperatures or prolonged exposure to sun may cause can to leak or swell. Once opened, remover should be used within six months or properly disposed of to avoid can deterioration. Do not store near flames or at elevated temperatures.

Keep container tightly closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	PEL: 25 ppm STEL: 125 ppm (15 min)	TLV: 50 ppm	No data.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
108-88-3	Toluene {Benzene, Methyl-; Toluol}	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 50 ppm	No data.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data.
64-17-5	Ethyl alcohol {Ethanol}	PEL: 1000 ppm	TLV: 1000 ppm	No data.
67-63-0	Isopropyl alcohol {sec-Propyl alcohol; IPA; 2-Propanol}	PEL: 400 ppm	TLV: 200 ppm STEL: 400 ppm	No data.

Respiratory Equipment (Specify Type):

For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved self-contained breathing apparatus or powered air supply respirator or loose fitting hood.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

Eye Protection:

Chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.

Protective Gloves:

Wear gloves with as much resistance to the chemical ingredients as possible. Laminate film gloves offer the best protection. Other glove materials, such as nitrile rubber, neoprene, and PVC will be degraded by methylene chloride, but may provide protection for some amount of time, based on the type of glove and the conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

Other Protective Clothing:

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly

SAFETY DATA SHEET
Goof Off All Purpose Paint Stripper

Page: 7
Printed: 04/20/2015
Revision: 04/16/2015
Supersedes Revision: 03/27/2015

**Engineering Controls
(Ventilation etc.):**

clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. If the work area is not well ventilated, DO NOT use this product. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas.

Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

**Work/Hygienic/Maintenance
Practices:**

Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Off-white opaque viscous liquid
Melting Point:	No data.
Boiling Point:	No data.
Autoignition Pt:	No data.
Flash Pt:	30.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: No data. UEL: No data.
Specific Gravity (Water = 1):	1.004
Density:	8.346 LB/GL
Vapor Pressure (vs. Air or mm Hg):	No data.
Vapor Density (vs. Air = 1):	> 1
Evaporation Rate:	< 1
Solubility in Water:	Slight
Viscosity:	1325 cps
pH:	8 - 10
Percent Volatile:	95.81 % by weight.
VOC / Volume:	25.1400 % WT

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 8
Printed: 04/20/2015
Revision: 04/16/2015
Supersedes Revision: 03/27/2015

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: Stable
Incompatibility - Materials To Avoid: Bases, oxygen, sodium, potassium, strong oxidizers, reactive metals, strong acids
Hazardous Decomposition Or Byproducts: Hydrogen chloride, chlorine, phosgene, carbon monoxide, carbon dioxide
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.

CAS# 75-09-2:
Tumorigenic Effects: TCl₀, Inhalation, Rat, 3500. PPM, 6 Y.
Result:
Tumorigenic: Carcinogenic by RTECS criteria.
Endocrine: Tumors.
- Fundamental and Applied Toxicology., Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 4,30, 1984

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.
Result:
Effects on Newborn: Growth statistics (e.g., reduced weight gain).
Effects on Newborn: Physical.
- Union Carbide Data Sheet, Union Carbide Corp., 39 Old Ridgebury Rd., Danbury, CT 06817, Vol/p/yr: 4/25, 1958

Standard Draize Test, Skin, Species: Rabbit, 810.0 MG, 24 H, Severe.
Result:
Specific Developmental Abnormalities: Musculoskeletal system.
- European Journal of Toxicology and Environmental Hygiene., For publisher information, see TOERD9, Paris France, Vol/p/yr: 9,171, 1976

CAS# 67-64-1:
Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.
Result:
Behavioral: Change in motor activity (specific assay).
Behavioral: Alteration of classical conditioning.
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 1330-20-7:
Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.
Result:
Behavioral: Muscle contraction or spasticity.

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 9

Printed: 04/20/2015

Revision: 04/16/2015

Supersedes Revision: 03/27/2015

Chronic Toxicological Effects:

Lungs, Thorax, or Respiration: Other changes.

- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.

Result:

Behavioral: General anesthetic.

Behavioral: Somnolence (general depressed activity).

Behavioral: Irritability.

- "Sbornik Vysledku Toxologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS# 108-88-3:

Reproductive Effects:, TClO, Inhalation, Rat, 800.0 MG/M3, 6 H, female 14-20 day(s) after conception.

Result:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Effects on Newborn: Behavioral.

- Brazilian Journal of Medical and Biological Research., Vol/p/yr: 23,533, 1990

Standard Draize Test, Eyes, Species: Rabbit, 2.000 MG, 24 H, Severe.

Result:

Effects on Embryo or Fetus: Other effects to embryo.

Specific Developmental Abnormalities: Eye, ear.

- Prehled Prumyslove Toxikologie, Marhold, J., Organicke Latky, Prague Czechoslovakia, Vol/p/yr: -,29, 1986

CAS# 100-41-4:

Tumorigenic Effects:, TClO, Inhalation, Rat, 750.0 ppm.

Result:

Tumorigenic: Carcinogenic by RTECS criteria.

Kidney, Ureter, Bladder: Tumors.

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Effects on Fertility: Litter size (e.g., # fetuses per litter; measured before birth).

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

This product has not been tested as a whole.

Carcinogenicity/Other Information:

IARC 2B - Possibly Carcinogenic to Humans

IARC 3: Not Classifiable as to Carcinogenicity in Humans

ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

ACGIH A4 - Not Classifiable as a Human Carcinogen.

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 10
 Printed: 04/20/2015
 Revision: 04/16/2015
 Supersedes Revision: 03/27/2015

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	Possible	2B	A3	Yes
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
108-88-3	Toluene {Benzene, Methyl-; Toluol}	n.a.	3	A4	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.
64-17-5	Ethyl alcohol {Ethanol}	n.a.	1	A4	n.a.
67-63-0	Isopropyl alcohol {sec-Propyl alcohol; IPA; 2-Propanol}	n.a.	3	A4	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: This product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with all applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material
DOT Hazard Class: 3 FLAMMABLE LIQUID
UN/NA Number: UN1263 **Packing Group:** II



Additional Transport Information: The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	No	Yes 1000 LB	Yes
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes 100 LB	Yes
108-88-3	Toluene {Benzene, Methyl-; Toluol}	No	Yes 1000 LB	Yes
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes 1000 LB	Yes
64-17-5	Ethyl alcohol {Ethanol}	No	No	No
67-63-0	Isopropyl alcohol {sec-Propyl alcohol; IPA; 2-Propanol}	No	No	Yes

This material meets the EPA 'Hazard Categories' defined Yes No Acute (immediate) Health Hazard
 Yes No Chronic (delayed) Health Hazard

SAFETY DATA SHEET

Goof Off All Purpose Paint Stripper

Page: 11

Printed: 04/20/2015

Revision: 04/16/2015

Supersedes Revision: 03/27/2015

for SARA Title III Sections Yes No Fire Hazard
311/312 as indicated: Yes No Sudden Release of Pressure Hazard
 Yes No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes
67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No
108-88-3	Toluene {Benzene, Methyl-; Toluol}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes
64-17-5	Ethyl alcohol {Ethanol}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
67-63-0	Isopropyl alcohol {sec-Propyl alcohol; IPA; 2-Propanol}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No

Regulatory Information Statement: All components of this material are listed on the TSCA Inventory or are exempt.

16. OTHER INFORMATION

Revision Date: 04/16/2015
Preparer Name: W.M. Barr EHS Dept (901)775-0100
Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.